

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 63-155044

(43)Date of publication of application : 28.06.1988

(51)Int.Cl.

G03C 1/00  
H01L 21/30

(21)Application number : 61-301610

(71)Applicant : FUJITSU LTD

(22)Date of filing : 19.12.1986

(72)Inventor : NAKAMURA HIROKO

TAKECHI SATOSHI

TSURUNAGA YUKARI

## (54) FORMATION OF RESIST PATTERN

## (57)Abstract:

PURPOSE: To prevent charge up by using a conductive film of poly $\beta$ -diketone as a flattening layer.

CONSTITUTION: The poly $\beta$ -diketone layer is formed as the flattening layer on a semiconductor substrate, for example, Al/Si substrate in formation of a resist pattern for which multi-layered resist layers having conductive films are used under a resist layer. After the resist layer is then formed, the layer is patterned. Since the poly $\beta$ -diketone has conductivity, the charge stagnating in the resist on the poly $\beta$ -diketone layer flows through the poly $\beta$ -diketone to the semiconductor substrate. The charge up is thereby prevented.

## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's  
decision of rejection]

[Date of requesting appeal against examiner's  
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office